



EMC Research Institute

66-6, Jeil-Ri, Yangji-Myun, Cheoin-Gu,
Yongin-Si, Gyeonggi-Do, Korea

Tel: 031-670-9600 Fax: 031-556-1114

EMC TEST REPORT

Page 1 of 34

Emission and Immunity of electromagnetic disturbance

Test Report No. : ERI-EN08-01170366

Equipment : Electric Strike

Name of basic model : DES-2200

Family model : None

Manufacturer : Doornics Co., Ltd

Applicant : Doornics Co., Ltd

Tested date : 2008. 06. 11. - 2008. 06. 12.

Testing Environment : Temperature: (21.0 - 24.0) °C, Relative Humidity: (30.4 - 43.0) % R.H.
Atmospheric pressure: (99.3 - 99.9) kPa

Receipt of date : 2008. 06. 05.

Issued date : 2008. 06. 13.

Test results : Pass

Test Standards : EN 61000-6-2 : 2005
EN 61000-6-3 : 2001

<u>Affirmation</u>	Measurements performed by	Approved by
	Title : Engineer Name : Kim, Young-sik	Title : Manager Name : Hur, Gweon

**EMC Research Institute**

2008. 06. 13.



The test results in this report relate only to the following EUT, and this report shall not be reproduced except in full, without the written approval of the laboratory.



Product Service

EC-Attestation of Compliance

No. E8N 08 06 44590 009

Holder of Certificate: Doornics Co., Ltd.

SK APT.-Factory No. 903, 16-4

Seongsu 1-Ga, Seongdong, Seoul 133-111

REPUBLIC OF KOREA

Name of Object: Locks
Electric strike**Model(s):** DES-2200**Description of Object:** Rated input voltage: 12/24 Vd.c.**Tested according to:** EN 61000-6-2:2005
EN 61000-6-3:2001

This EC-Attestation of Compliance is issued according to the Directive 2004/108/EC relating to electromagnetic compatibility on a voluntary basis. It confirms that the listed apparatus complies with all essential requirements of the EMC directive and applies only to the sample and its technical documentation submitted to TÜV SÜD Product Service GmbH for testing and certification. See also notes overleaf.

Test report no.: ERI-EN08-01170366**Date,** 2008-06-13

CE After preparation of the necessary technical documentation as well as the conformity declaration the required CE marking can be affixed on the product. Other relevant directives have to be observed.